

## 8. Combination and the data

### 3U55S2SR2FA combination and the data COOLING 5.5

Comb.	Combinations			Rated capacity(kW) (Nom. cooling)			Total cooling capacity(kW)			Total power input (kW)			Total current (A)@230V			EER (W/W)	ENERGY LABEL	SEER (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit A	Unit B	Unit C	min. data	rated data	max. data	min. data	rated data	max. data	min. data	rated data	max. data	rated capacity				
1x1	2.0	—	—	2.00	—	—	0.80	2.00	2.80	0.55	0.62	1.50	2.44	2.75	6.65	3.23	A	6.50	A++	not available
	2.5	—	—	2.60	—	—	0.80	2.60	3.90	0.55	0.78	1.65	2.44	3.46	7.32	3.33	A	6.50	A++	not available
	3.5	—	—	3.60	—	—	1.00	3.60	5.30	0.55	1.07	1.76	2.44	4.75	7.81	3.36	A	6.50	A++	not available
	4.2	—	—	4.40	—	—	1.30	4.40	5.00	0.55	1.28	2.15	2.44	5.68	9.54	3.44	A	6.50	A++	not available
	5.0	—	—	5.2	—	—	1.40	5.2	7.00	0.55	1.48	2.24	2.44	6.57	9.94	3.51	A	6.50	A++	not available
	2.0	2.0	—	2.00	2.00	—	1.60	4.00	5.60	0.55	1.18	2.50	2.44	5.24	11.09	3.39	A	6.60	A++	available
BI (1x2)	2.0	2.5	—	2.00	2.60	—	1.80	4.60	6.70	0.55	1.32	2.50	2.44	5.86	11.09	3.48	A	6.70	A++	available
	2.0	3.5	—	1.96	3.54	—	2.10	5.50	7.00	0.55	1.55	2.50	2.44	6.88	11.09	3.55	A	6.80	A++	available
	2.0	4.2	—	1.72	3.78	—	2.10	5.50	7.00	0.55	1.54	2.50	2.44	6.83	11.09	3.57	A	6.80	A++	available
	2.0	5.0	—	1.53	3.97	—	2.10	5.50	7.00	0.55	1.54	2.50	2.44	6.83	11.09	3.57	A	6.80	A++	available
	2.5	2.5	—	2.60	2.60	—	2.00	5.20	7.00	0.55	1.49	2.50	2.44	6.61	11.09	3.49	A	6.80	A++	available
	2.5	3.5	—	2.18	3.02	—	2.10	5.20	7.00	0.55	1.53	2.50	2.44	6.79	11.09	3.40	A	6.30	A++	available
	2.5	4.2	—	2.04	3.46	—	2.10	5.50	7.00	0.55	1.52	2.50	2.44	6.74	11.09	3.62	A	6.80	A++	not available
	2.5	5.0	—	1.83	3.67	—	2.10	5.50	7.00	0.55	1.50	2.50	2.44	6.65	11.09	3.67	A	6.80	A++	available
	3.5	3.5	—	2.75	2.75	—	2.10	5.50	7.00	0.55	1.50	2.50	2.44	6.65	11.09	3.67	A	6.80	A++	available
	2.0	2.0	2.0	1.83	1.83	1.83	2.10	5.50	7.00	0.55	1.45	2.50	2.44	6.43	11.09	3.79	A	7.20	A++	available
	2.0	2.0	2.5	1.67	1.67	2.17	2.10	5.50	7.00	0.55	1.45	2.50	2.44	6.43	11.09	3.79	A	7.20	A++	available
	2.0	2.0	3.5	1.45	1.45	2.61	2.10	5.50	7.00	0.55	1.43	2.50	2.44	6.34	11.09	3.85	A	7.30	A++	available
2.0	2.5	2.5	1.53	1.99	1.99	2.10	5.50	7.00	0.55	1.43	2.50	2.44	6.34	11.09	3.85	A	7.40	A++	available	
TRI (1x3)	2.0	2.5	3.5	1.34	1.74	2.41	2.10	5.50	7.00	0.55	1.42	2.50	2.44	6.30	11.09	3.87	A	7.40	A++	available
	2.5	2.5	2.5	1.83	1.83	1.83	2.10	5.50	7.00	0.55	1.37	2.50	2.44	6.08	11.09	4.01	A	7.50	A++	available
	2.0	2.0	3.5	1.45	1.45	2.61	2.10	5.50	7.00	0.55	1.43	2.50	2.44	6.34	11.09	3.85	A	7.30	A++	available
	2.0	2.5	2.5	1.53	1.99	1.99	2.10	5.50	7.00	0.55	1.43	2.50	2.44	6.34	11.09	3.85	A	7.40	A++	available
	2.0	2.5	3.5	1.34	1.74	2.41	2.10	5.50	7.00	0.55	1.42	2.50	2.44	6.30	11.09	3.87	A	7.40	A++	available
	2.5	2.5	2.5	1.83	1.83	1.83	2.10	5.50	7.00	0.55	1.37	2.50	2.44	6.08	11.09	4.01	A	7.50	A++	available

## 3U55S2SR2FA combination and the data HEATING 6.8

Comb.	Combinations			Rated capacity(kW) (Nom. heating)			Total heating capacity(kW)			Total power input (W)			Total current (A)@230V			COP (W/W)	ENERGY LABEL	SCOP (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit A	Unit B	Unit C	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
1x1	2.0	—	—	2.30	—	—	0.80	2.30	4.00	0.55	0.63	1.80	2.44	2.80	7.99	3.65	A	3.50	A	not available
	2.5	—	—	3.60	—	—	0.80	3.60	6.00	0.55	0.98	1.90	2.44	4.35	8.43	3.67	A	3.50	A	not available
	3.5	—	—	4.50	—	—	1.00	4.50	6.00	0.55	1.20	2.00	2.44	5.32	8.87	3.75	A	3.50	A	not available
	4.2	—	—	5.40	—	—	1.50	5.40	6.00	0.55	1.40	2.00	2.44	6.21	8.87	3.86	A	3.60	A	not available
	5.0	—	—	6.00	—	—	1.50	6.00	7.60	0.55	1.55	2.20	2.44	6.88	9.76	3.87	A	3.60	A	not available
BI (1x2)	2.0	2.0	—	2.30	2.30	—	1.20	4.60	7.60	0.55	1.25	2.10	2.44	5.55	9.32	3.68	A	3.70	A	available
	2.0	2.5	—	2.30	3.60	—	1.20	5.90	7.60	0.55	1.54	2.10	2.44	6.83	9.32	3.83	A	3.75	A	available
	2.0	3.5	—	2.30	4.50	—	1.20	6.80	7.60	0.55	1.72	2.10	2.44	7.63	9.32	3.95	A	3.75	A	available
	2.0	4.2	—	2.03	4.77	—	1.70	6.80	7.60	0.55	1.70	2.10	2.44	7.54	9.32	4.00	A	3.75	A	available
	2.0	5.0	—	1.88	4.92	—	1.70	6.80	7.60	0.55	1.70	2.10	2.44	7.54	9.32	4.00	A	3.75	A	available
	2.5	2.5	—	3.40	3.40	—	1.70	6.80	7.60	0.55	1.68	2.20	2.44	7.45	9.76	4.05	A	3.80	A	available
	2.5	3.5	—	2.89	3.61	—	1.70	6.50	7.60	0.55	1.68	2.20	2.44	7.45	9.76	3.87	A	3.80	A	available
	2.5	4.2	—	2.72	4.08	—	1.70	6.80	7.60	0.55	1.66	2.20	2.44	7.36	9.76	4.10	A	3.80	A	not available
	2.5	5.0	—	2.55	4.25	—	1.70	6.80	7.60	0.55	1.66	2.20	2.44	7.36	9.76	4.10	A	3.85	A	available
	3.5	3.5	—	3.40	3.40	—	1.70	6.80	7.60	0.55	1.66	2.20	2.44	7.36	9.76	4.10	A	3.85	A	available
TRI (1x3)	2.0	2.0	2.0	2.27	2.27	2.27	1.70	6.80	7.60	0.55	1.64	2.20	2.44	7.28	9.76	4.15	A	3.90	A	available
	2.0	2.0	2.5	1.91	1.91	2.99	1.70	6.80	7.60	0.55	1.63	2.20	2.44	7.23	9.76	4.17	A	3.90	A	available
	2.0	2.0	3.5	1.72	1.72	3.36	1.70	6.80	7.60	0.55	1.63	2.20	2.44	7.23	9.76	4.17	A	3.90	A	available
	2.0	2.5	2.5	1.65	2.58	2.58	1.70	6.80	7.60	0.55	1.62	2.20	2.44	7.19	9.76	4.20	A	3.95	A	available
	2.0	2.5	3.5	1.50	2.35	2.94	1.70	6.80	7.60	0.55	1.62	2.20	2.44	7.19	9.76	4.20	A	3.95	A	available
	2.5	2.5	2.5	2.27	2.27	2.27	1.70	6.80	7.60	0.55	1.55	2.20	2.44	6.88	9.76	4.39	A	4.00	A+	available

**3U70S2SR2FA combination and the data**  
**COOLING 7**

Comb.	Combinations			Rated capacity(kW) (Nom. cooling)			Total cooling capacity(kW)			Total power input (kW)			Total current (A)@230V			EER (W/W)	ENERGY LABEL	SEER (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit A	Unit B	Unit C	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
1x1	2.0	—	—	2.00	—	—	0.80	2.00	2.80	0.55	0.62	1.30	2.44	2.75	5.8	3.23	A	6.40	A++	not available
	2.5	—	—	2.60	—	—	0.80	2.60	3.90	0.55	0.79	1.34	2.44	3.50	5.9	3.29	A	6.40	A++	not available
	3.5	—	—	3.60	—	—	1.00	3.60	5.30	0.55	1.09	1.65	2.44	4.84	7.3	3.30	A	6.40	A++	not available
	4.2	—	—	4.40	—	—	1.30	4.40	5.00	0.55	1.32	1.90	2.44	5.86	8.43	3.33	A	6.40	A++	not available
	5.0	—	—	5.20	—	—	1.40	5.20	7.00	0.55	1.55	2.00	2.44	6.88	8.9	3.35	A	6.40	A++	not available
	7.1	—	—	6.50	—	—	1.50	6.50	7.40	0.55	1.92	2.60	2.44	8.52	11.5	3.39	A	6.40	A++	not available
BI (1x2)	2.0	2.0	—	2.00	2.00	—	1.80	4.00	5.60	0.55	1.21	2.60	2.44	5.37	11.5	3.31	A	6.60	A++	available
	2.0	2.5	—	2.00	2.60	—	1.80	4.60	6.70	0.55	1.35	2.64	2.44	5.99	11.7	3.41	A	6.60	A++	available
	2.0	3.5	—	2.00	3.60	—	1.80	5.60	7.50	0.55	1.65	2.95	2.44	7.32	13.1	3.39	A	6.60	A++	available
	2.0	4.2	—	2.00	4.40	—	1.80	6.40	7.60	0.55	1.89	3.00	2.44	8.39	13.3	3.39	A	6.70	A++	not available
	2.0	5.0	—	1.94	5.06	—	2.40	7.00	7.60	0.55	2.02	3.00	2.44	8.96	13.3	3.47	A	6.70	A++	available
	2.5	2.5	—	2.60	2.60	—	2.00	5.20	7.40	0.55	1.52	2.68	2.44	6.74	11.9	3.42	A	6.70	A++	available
	2.5	3.5	—	2.60	3.60	—	2.00	6.20	7.60	0.55	1.79	2.99	2.44	7.94	13.3	3.46	A	6.70	A++	available
	2.5	4.2	—	2.60	4.40	—	2.40	7.00	7.60	0.55	2.02	3.00	2.44	8.96	13.3	3.47	A	6.70	A++	not available
	2.5	5.0	—	2.33	4.67	—	2.40	7.00	7.60	0.55	2.00	3.00	2.44	8.87	13.3	3.50	A	6.70	A++	available
	3.5	3.5	—	3.40	3.40	—	2.40	6.80	7.60	0.55	2.00	3.20	2.44	8.87	14.2	3.40	A	6.20	A++	available
	3.5	4.2	—	3.15	3.85	—	2.40	7.00	7.60	0.55	1.82	3.20	2.44	8.07	14.2	3.85	A	6.80	A++	not available
	3.5	5.0	—	2.86	4.14	—	2.40	7.00	7.60	0.55	1.82	3.20	2.44	8.07	14.2	3.85	A	6.80	A++	available
	4.2	4.2	—	3.50	3.50	—	2.40	7.00	7.60	0.55	1.82	3.20	2.44	8.07	14.2	3.85	A	6.80	A++	not available
	TRI (1x3)	2.0	2.0	2.0	2.00	2.00	2.00	2.40	6.00	7.60	0.55	1.75	2.70	2.44	7.76	12.0	3.43	A	7.20	A++
2.0		2.0	2.5	2.00	2.00	2.60	2.40	6.60	7.60	0.55	1.75	2.70	2.44	7.76	12.0	3.77	A	7.20	A++	available
2.0		2.0	3.5	1.84	1.84	3.32	2.40	7.00	7.60	0.55	1.80	2.70	2.44	7.99	12.0	3.89	A	7.20	A++	available
2.0		2.0	4.2	1.67	1.67	3.67	2.40	7.00	7.60	0.55	1.80	2.70	2.44	7.99	12.0	3.89	A	7.20	A++	not available
2.0		2.0	5.0	1.52	1.52	3.96	2.40	7.00	7.60	0.55	1.80	2.70	2.44	7.99	12.0	3.89	A	7.20	A++	available
2.0		2.5	2.5	1.94	2.53	2.53	2.40	7.00	7.60	0.55	1.80	2.70	2.44	7.99	12.0	3.89	A	7.30	A++	available
2.0		2.5	3.5	1.71	2.22	3.07	2.40	7.00	7.60	0.55	1.80	2.70	2.44	7.99	12.0	3.89	A	7.30	A++	available
2.0		2.5	4.2	1.56	2.02	3.42	2.40	7.00	7.60	0.55	1.80	2.70	2.44	7.99	12.0	3.89	A	7.30	A++	not available
2.0		2.5	5.0	1.43	1.86	3.71	2.40	7.00	7.60	0.55	1.82	2.70	2.44	8.07	12.0	3.85	A	7.30	A++	available
2.0		3.5	3.5	1.52	2.74	2.74	2.40	7.00	7.60	0.55	1.82	2.70	2.44	8.07	12.0	3.85	A	7.40	A++	available
2.0		3.5	4.2	1.40	2.52	3.08	2.40	7.00	7.60	0.55	1.80	2.70	2.44	7.99	12.0	3.89	A	7.40	A++	not available
2.5		2.5	2.5	2.33	2.33	2.33	2.40	7.00	7.60	0.55	1.76	2.70	2.44	7.81	12.0	3.98	A	7.50	A++	available
2.5		2.5	3.5	2.07	2.07	2.86	2.40	7.00	7.60	0.55	1.78	2.70	2.44	7.90	12.0	3.93	A	7.50	A++	available
2.5		2.5	4.2	1.90	1.90	3.21	2.40	7.00	7.60	0.55	1.78	2.70	2.44	7.90	12.0	3.93	A	7.50	A++	not available
2.5		3.5	3.5	1.86	2.57	2.57	2.40	7.00	7.60	0.55	1.78	2.70	2.44	7.90	12.0	3.93	A	7.50	A++	available

## 3U70S2SR2FA combination and the data HEATING 7.6

Comb.	Combinations			Rated capacity(kW) (Nom. heating)			Total heating capacity(kW)			Total power input (W)			Total current (A)@230V			COP (W/W)	ENERGY LABEL	SCOP (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit A	Unit B	Unit C	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
1x1	2.0	—	—	2.30	—	—	0.80	2.30	4.00	0.55	0.64	1.40	2.44	2.83	6.21	3.61	A	3.70	A	not available
	2.5	—	—	3.60	—	—	0.80	3.60	6.00	0.55	0.98	1.50	2.44	4.35	6.65	3.67	A	3.70	A	not available
	3.5	—	—	4.50	—	—	1.00	4.50	6.00	0.55	1.22	1.65	2.44	5.41	7.32	3.69	A	3.70	A	not available
	4.2	—	—	5.40	—	—	1.50	5.40	6.00	0.55	1.45	1.90	2.44	6.43	8.43	3.72	A	3.70	A	not available
	5.0	—	—	6.00	—	—	1.50	6.00	8.00	0.55	1.60	2.00	2.44	7.10	8.87	3.75	A	3.70	A	not available
BI (1x2)	7.1	—	—	7.00	—	—	1.50	7.00	8.60	0.55	1.84	2.20	2.44	8.16	9.76	3.80	A	3.70	A	not available
	2.0	2.0	—	2.30	2.30	—	2.60	4.60	8.00	0.55	1.25	2.00	2.44	5.55	8.87	3.68	A	3.80	A	available
	2.0	2.5	—	2.30	3.60	—	2.70	5.90	8.50	0.55	1.60	2.00	2.44	7.10	8.87	3.69	A	3.80	A	available
	2.0	3.5	—	2.30	4.50	—	2.70	6.80	8.50	0.55	1.82	2.10	2.44	8.07	9.32	3.74	A	3.80	A	available
	2.0	4.2	—	2.27	5.33	—	2.90	7.60	8.50	0.55	2.06	2.10	2.44	9.14	9.32	3.69	A	3.90	A	not available
	2.0	5.0	—	2.11	5.49	—	2.90	7.60	8.50	0.55	2.05	2.10	2.44	9.09	9.32	3.71	A	3.90	A	available
	2.5	2.5	—	3.60	3.60	—	2.90	7.20	8.50	0.55	1.93	2.10	2.44	8.56	9.32	3.73	A	3.90	A	available
	2.5	3.5	—	3.38	4.22	—	2.90	7.60	8.50	0.55	2.05	2.10	2.44	9.09	9.32	3.71	A	3.90	A	available
	2.5	4.2	—	3.04	4.56	—	2.90	7.60	8.50	0.55	2.06	2.10	2.44	9.14	9.32	3.69	A	3.95	A	not available
	2.5	5.0	—	2.85	4.75	—	2.90	7.60	8.50	0.55	2.05	2.10	2.44	9.09	9.32	3.71	A	3.95	A	available
TRI (1x3)	3.5	3.5	—	3.75	3.75	—	2.90	7.50	8.50	0.55	1.93	2.20	2.44	8.54	9.76	3.90	A	3.80	A	available
	3.5	4.2	—	3.45	4.15	—	2.90	7.60	8.50	0.55	2.02	2.20	2.44	8.96	9.76	3.76	A	4.00	A+	not available
	3.5	5.0	—	3.26	4.34	—	2.90	7.60	8.50	0.55	2.00	2.20	2.44	8.87	9.76	3.80	A	4.00	A+	available
	4.2	4.2	—	3.80	3.80	—	2.90	7.60	8.50	0.55	2.00	2.20	2.44	8.87	9.76	3.80	A	4.00	A+	not available
	2.0	2.0	2.0	2.30	2.30	2.30	2.90	6.90	8.50	0.55	1.85	2.30	2.44	8.21	10.20	3.73	A	4.05	A+	available
	2.0	2.0	2.5	2.13	2.13	3.34	2.90	7.60	8.50	0.55	1.98	2.30	2.44	8.78	10.20	3.84	A	4.05	A+	available
	2.0	2.0	3.5	1.92	1.92	3.76	2.90	7.60	8.50	0.55	1.96	2.30	2.44	8.70	10.20	3.88	A	4.05	A+	available
	2.0	2.0	4.2	1.75	1.75	4.10	2.90	7.60	8.50	0.55	1.95	2.30	2.44	8.65	10.20	3.90	A	4.05	A+	not available
	2.0	2.0	5.0	1.65	1.65	4.30	2.90	7.60	8.50	0.55	1.95	2.30	2.44	8.65	10.20	3.90	A	4.05	A+	available
	2.0	2.5	2.5	1.84	2.88	2.88	2.90	7.60	8.50	0.55	1.90	2.30	2.44	8.43	10.20	4.00	A	4.08	A+	available
	2.0	2.5	3.5	1.68	2.63	3.29	2.90	7.60	8.50	0.55	1.85	2.30	2.44	8.21	10.20	4.11	A	4.08	A+	available
	2.0	2.5	4.2	1.55	2.42	3.63	2.90	7.60	8.50	0.55	1.85	2.30	2.44	8.21	10.20	4.11	A	4.08	A+	not available
	2.0	2.5	5.0	1.47	2.30	3.83	2.90	7.60	8.50	0.55	1.86	2.30	2.44	8.25	10.20	4.09	A	4.08	A+	available
	2.0	3.5	3.5	1.55	3.03	3.03	2.90	7.60	8.50	0.55	1.88	2.30	2.44	8.34	10.20	4.04	A	4.10	A+	available
	2.0	3.5	4.2	1.43	2.80	3.36	2.90	7.60	8.50	0.55	1.85	2.30	2.44	8.21	10.20	4.11	A	4.10	A+	not available
	2.5	2.5	2.5	2.53	2.53	2.53	2.90	7.60	8.50	0.55	1.81	2.30	2.44	8.03	10.20	4.20	A	4.20	A+	available
	2.5	2.5	3.5	2.34	2.34	2.92	2.90	7.60	8.50	0.55	1.84	2.30	2.44	8.16	10.20	4.13	A	4.20	A+	available
	2.5	2.5	4.2	2.17	2.17	3.26	2.90	7.60	8.50	0.55	1.84	2.30	2.44	8.16	10.20	4.13	A	4.20	A+	not available
2.5	3.5	3.5	2.17	2.71	2.71	2.90	7.60	8.50	0.55	1.84	2.30	2.44	8.16	10.20	4.13	A	4.20	A+	available	

**4U75S2SR2FA combination and the data**  
**COOLING 7.5**

Comb.	Combinations				Rated capacity output/kW (Nom. cooling)				Total cooling capacity(kW)			Total power input (kW)			Total current (A)@230V			EER (W/W)	ENERGY LABEL	SEER (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
1x1	2.0	—	—	—	2.00	—	—	—	0.80	2.00	2.80	0.55	0.66	1.30	2.44	2.93	5.77	3.03	B	6.20	A++	not available
	2.5	—	—	—	2.60	—	—	—	0.80	2.60	3.90	0.55	0.86	1.34	2.44	3.82	5.93	3.02	B	6.20	A++	not available
	3.5	—	—	—	3.60	—	—	—	1.00	3.60	5.30	0.55	1.20	1.50	2.44	5.32	6.65	3.00	B	6.20	A++	not available
	4.2	—	—	—	4.40	—	—	—	1.30	4.40	5.00	0.55	1.40	1.90	2.44	6.21	8.43	3.14	B	6.20	A++	not available
	5.0	—	—	—	5.20	—	—	—	1.40	5.20	7.00	0.55	1.65	1.90	2.44	7.32	8.43	3.15	B	6.20	A++	not available
	7.1	—	—	—	6.50	—	—	—	1.50	6.50	7.40	0.55	2.05	2.80	2.44	9.09	12.42	3.17	B	6.20	A++	not available
BI (1x2)	2.0	2.0	—	—	2.00	2.00	—	—	2.00	4.00	5.60	0.55	1.30	3.00	2.44	5.77	13.31	3.08	B	6.20	A++	available
	2.0	2.5	—	—	2.00	2.60	—	—	2.00	4.60	6.70	0.55	1.50	3.00	2.44	6.65	13.31	3.07	B	6.20	A++	available
	2.0	3.5	—	—	2.00	3.60	—	—	2.00	5.60	8.10	0.55	1.80	3.00	2.44	7.99	13.31	3.11	B	6.20	A++	available
	2.0	4.2	—	—	2.00	4.40	—	—	2.00	6.40	7.80	0.55	1.95	3.00	2.44	8.65	13.31	3.28	A	6.20	A++	not available
	2.0	5.0	—	—	2.00	5.20	—	—	2.00	7.20	8.70	0.55	2.20	3.00	2.44	9.76	13.31	3.27	A	6.20	A++	available
	2.0	7.1	—	—	1.76	5.74	—	—	2.00	7.50	8.70	0.55	2.24	3.10	2.44	9.94	13.75	3.35	A	6.20	A++	available
	2.5	2.5	—	—	2.60	2.60	—	—	2.00	5.20	7.80	0.55	1.70	3.10	2.44	7.54	13.75	3.06	B	6.20	A++	available
	2.5	3.5	—	—	2.60	3.60	—	—	2.00	6.20	8.70	0.55	2.00	3.10	2.44	8.87	13.75	3.10	B	6.20	A++	available
	2.5	4.2	—	—	2.60	4.40	—	—	2.00	7.00	8.70	0.55	2.10	3.10	2.44	9.32	13.75	3.33	A	6.20	A++	not available
	2.5	5.0	—	—	2.50	5.00	—	—	2.00	7.50	8.70	0.55	2.24	3.10	2.44	9.94	13.75	3.35	A	6.20	A++	available
	2.5	7.1	—	—	2.14	5.36	—	—	2.00	7.50	8.70	0.55	2.24	3.10	2.44	9.94	13.75	3.35	A	6.20	A++	available
	3.5	3.5	—	—	3.60	3.60	—	—	2.00	7.20	8.70	0.55	2.20	3.10	2.44	9.76	13.75	3.27	A	6.20	A++	available
	3.5	4.2	—	—	3.38	4.13	—	—	2.00	7.50	8.70	0.55	2.26	3.20	2.44	10.03	14.20	3.32	A	6.20	A++	not available
	3.5	5.0	—	—	2.95	4.25	—	—	2.00	7.20	8.70	0.55	2.24	3.20	2.44	9.94	14.20	3.21	A	6.20	A++	available
	3.5	7.1	—	—	2.67	4.83	—	—	2.00	7.50	8.70	0.55	2.25	3.20	2.44	9.98	14.20	3.33	A	6.20	A++	available
	4.2	4.2	—	—	3.75	3.75	—	—	2.00	7.50	8.70	0.55	2.25	3.20	2.44	9.98	14.20	3.33	A	6.20	A++	not available
	4.2	5.0	—	—	3.44	4.06	—	—	2.00	7.50	8.70	0.55	2.25	3.20	2.44	9.98	14.20	3.33	A	6.20	A++	not available
	4.2	7.1	—	—	3.03	4.47	—	—	2.00	7.50	8.70	0.55	2.25	3.30	2.44	9.98	14.64	3.33	A	6.20	A++	not available
	5.0	5.0	—	—	3.75	3.75	—	—	2.00	7.50	8.70	0.55	2.18	3.30	2.44	9.67	14.64	3.44	A	6.20	A++	available
	5.0	7.1	—	—	3.33	4.17	—	—	2.00	7.50	8.70	0.55	2.18	3.30	2.44	9.67	14.64	3.44	A	6.20	A++	available
7.1	7.1	—	—	4.25	4.25	—	—	2.50	8.50	9.50	0.55	2.55	3.30	2.44	11.31	14.64	3.33	A	6.20	A++	available	

Comb.	Combinations				Rated capacity output/ kW (Nom. cooling)				Total cooling capacity(kW)			Total power input (kW)			Total current (A)@230V			EER (W/W)	ENERGY LABEL	SEER (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
TRI (1x3)	2.0	2.0	2.0	—	2.00	2.00	2.00	—	2.40	6.00	8.70	0.55	1.80	3.40	2.44	7.99	15.08	3.33	A	6.70	A++	available
	2.0	2.0	2.5	—	2.00	2.00	2.60	—	2.40	6.60	8.70	0.55	1.95	3.40	2.44	8.65	15.08	3.38	A	6.70	A++	available
	2.0	2.0	3.5	—	1.97	1.97	3.55	—	2.40	7.50	8.70	0.55	2.20	3.40	2.44	9.76	15.08	3.41	A	6.70	A++	not available
	2.0	2.0	4.2	—	1.79	1.79	3.93	—	2.40	7.50	8.70	0.55	2.20	3.40	2.44	9.76	15.08	3.41	A	6.70	A++	available
	2.0	2.0	5.0	—	1.63	1.63	4.24	—	2.40	7.50	8.70	0.55	2.20	3.40	2.44	9.76	15.08	3.41	A	6.70	A++	available
	2.0	2.0	7.1	—	1.43	1.43	4.64	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	available
	2.0	2.5	2.5	—	2.00	2.60	2.60	—	2.40	7.20	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.35	A	6.70	A++	available
	2.0	2.5	3.5	—	1.83	2.38	3.29	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	not available
	2.0	2.5	4.2	—	1.67	2.17	3.67	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	available
	2.0	2.5	5.0	—	1.53	1.99	3.98	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	available
	2.0	2.5	7.1	—	1.35	1.76	4.39	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	available
	2.0	3.5	3.5	—	1.63	2.93	2.93	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	not available
	2.0	3.5	4.2	—	1.50	2.70	3.30	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	available
	2.0	3.5	5.0	—	1.39	2.50	3.61	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	available
	2.0	3.5	7.1	—	1.24	2.23	4.03	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	not available
	2.0	4.2	4.2	—	1.39	3.06	3.06	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	not available
	2.0	4.2	5.0	—	1.29	2.84	3.36	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	not available
	2.0	4.2	7.1	—	1.16	2.56	3.78	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	available
	2.5	2.5	2.5	—	2.50	2.50	2.50	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.72	A++	available
	2.5	2.5	3.5	—	2.22	2.22	3.07	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.72	A++	not available
	2.5	2.5	4.2	—	2.03	2.03	3.44	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.74	A++	available
	2.5	2.5	5.0	—	1.88	1.88	3.75	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.74	A++	available
	2.5	2.5	7.1	—	1.67	1.67	4.17	—	2.40	7.50	8.70	0.55	2.15	3.40	2.44	9.54	15.08	3.49	A	6.70	A++	available
	2.5	3.5	3.5	—	1.99	2.76	2.76	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.73	A++	not available
	2.5	3.5	4.2	—	1.84	2.55	3.11	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.70	A++	available
	2.5	3.5	5.0	—	1.71	2.37	3.42	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.70	A++	available
	2.5	3.5	7.1	—	1.54	2.13	3.84	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.70	A++	not available
	2.5	4.2	4.2	—	1.71	2.89	2.89	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.70	A++	not available
	2.5	4.2	5.0	—	1.60	2.70	3.20	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.70	A++	not available
	3.5	3.5	3.5	—	2.50	2.50	2.50	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.75	A++	available
3.5	3.5	4.2	—	2.33	2.33	2.84	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.70	A++	not available	
3.5	3.5	5.0	—	2.18	2.18	3.15	—	2.40	7.50	8.70	0.55	2.08	3.40	2.44	9.23	15.08	3.61	A	6.70	A++	available	

Comb.	Combinations				Rated capacity output/ kW (Nom. cooling)				Total cooling capacity(kW)			Total power input (kW)			Total current (A)@230V			EER (W/W)	ENERGY LABEL	SEER (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
QUADRI (1x4)	2.0	2.0	2.0	2.0	1.88	1.88	1.88	1.88	2.40	7.50	8.70	0.55	2.12	3.40	2.44	9.41	15.08	3.54	A	6.80	A++	available
	2.0	2.0	2.0	2.5	1.74	1.74	1.74	2.27	2.40	7.50	8.70	0.55	2.12	3.40	2.44	9.41	15.08	3.54	A	6.80	A++	available
	2.0	2.0	2.0	3.5	1.56	1.56	1.56	2.81	2.40	7.50	8.70	0.55	2.12	3.40	2.44	9.41	15.08	3.54	A	6.80	A++	available
	2.0	2.0	2.0	4.2	1.44	1.44	1.44	3.17	2.40	7.50	8.70	0.55	2.12	3.40	2.44	9.41	15.08	3.54	A	6.80	A++	not available
	2.0	2.0	2.0	5.0	1.34	1.34	1.34	3.48	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.80	A++	available
	2.0	2.0	2.0	7.1	1.20	1.20	1.20	3.90	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.70	A++	available
	2.0	2.0	2.5	2.5	1.63	1.63	2.12	2.12	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.80	A++	available
	2.0	2.0	2.5	3.5	1.47	1.47	1.91	2.65	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.80	A++	available
	2.0	2.0	2.5	4.2	1.36	1.36	1.77	3.00	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.80	A++	not available
	2.0	2.0	2.5	5.0	1.27	1.27	1.65	3.31	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.80	A++	available
	2.0	2.0	2.5	7.1	1.15	1.15	1.49	3.72	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.70	A++	available
	2.0	2.0	3.5	3.5	1.34	1.34	2.41	2.41	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.80	A++	available
	2.0	2.0	3.5	4.2	1.25	1.25	2.25	2.75	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.70	A++	not available
	2.0	2.0	3.5	5.0	1.17	1.17	2.11	3.05	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	6.70	A++	available
	2.0	2.0	4.2	4.2	1.17	1.17	2.58	2.58	2.40	7.50	8.70	0.55	2.02	3.40	2.44	8.96	15.08	3.71	A	7.00	A++	not available
	2.0	2.0	4.2	5.0	1.10	1.10	2.43	2.87	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	not available
	2.0	2.5	2.5	2.5	1.53	1.99	1.99	1.99	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	available
	2.0	2.5	2.5	3.5	1.39	1.81	1.81	2.50	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	available
	2.0	2.5	2.5	4.2	1.29	1.68	1.68	2.84	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	not available
	2.0	2.5	2.5	5.0	1.21	1.57	1.57	3.15	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	available
	2.0	2.5	3.5	3.5	1.27	1.65	2.29	2.29	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	available
	2.0	2.5	3.5	4.2	1.19	1.55	2.14	2.62	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	not available
	2.0	2.5	3.5	5.0	1.12	1.46	2.01	2.91	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	available
	2.0	2.5	4.2	4.2	1.12	1.46	2.46	2.46	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	not available
	2.0	2.5	4.2	5.0	1.06	1.37	2.32	2.75	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	not available
	2.0	3.5	3.5	3.5	1.17	2.11	2.11	2.11	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	available
	2.0	3.5	3.5	4.2	1.10	1.99	1.99	2.43	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	not available
	2.5	2.5	2.5	2.5	1.88	1.88	1.88	1.88	2.40	7.50	8.70	0.55	2.00	3.40	2.44	8.87	15.08	3.75	A	7.00	A++	available
	2.5	2.5	2.5	3.5	1.71	1.71	1.71	2.37	2.40	7.50	8.70	0.55	1.97	3.40	2.44	8.74	15.08	3.81	A	7.00	A++	available
	2.5	2.5	2.5	4.2	1.60	1.60	1.60	2.70	2.40	7.50	8.70	0.55	1.97	3.40	2.44	8.74	15.08	3.81	A	7.00	A++	not available
2.5	2.5	3.5	3.5	1.57	1.57	2.18	2.18	2.40	7.50	8.70	0.55	1.97	3.40	2.44	8.74	15.08	3.81	A	7.00	A++	available	

## 4U75S2SR2FA combination and the data HEATING 8.6

Comb.	Combinations				Rated capacity output/kW (Nom. heating)				Total heating capacity(KW)			Total power input(W)			Total current (A)@230V			COP (W/W)	ENERGY LABEL	SCOP (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
1x1	2.0	—	—	—	2.30	—	—	—	0.80	2.30	4.00	0.55	0.63	1.50	2.44	2.80	6.65	3.65	A	3.70	A	not available
	2.5	—	—	—	3.60	—	—	—	0.80	3.60	6.00	0.55	0.98	1.40	2.44	4.35	6.21	3.67	A	3.70	A	not available
	3.5	—	—	—	4.50	—	—	—	1.00	4.50	6.00	0.55	1.21	1.50	2.44	5.37	6.65	3.72	A	3.70	A	not available
	4.2	—	—	—	5.40	—	—	—	1.50	5.40	6.00	0.55	1.44	1.90	2.44	6.39	8.43	3.75	A	3.70	A	not available
	5.0	—	—	—	6.00	—	—	—	1.50	6.00	8.00	0.55	1.59	2.60	2.44	7.05	11.54	3.77	A	3.70	A	not available
	7.1	—	—	—	7.00	—	—	—	1.50	7.00	8.60	0.55	1.83	2.60	2.44	8.12	11.54	3.83	A	3.70	A	not available
BI (1x2)	2.0	2.0	—	—	2.30	2.30	—	—	2.80	4.60	8.00	0.55	1.25	2.90	2.44	5.55	12.87	3.68	A	3.75	A	available
	2.0	2.5	—	—	2.30	3.60	—	—	2.80	5.90	9.00	0.55	1.59	2.90	2.44	7.05	12.87	3.71	A	3.75	A	available
	2.0	3.5	—	—	2.30	4.50	—	—	2.80	6.80	10.00	0.55	1.83	2.90	2.44	8.12	12.87	3.72	A	3.75	A	available
	2.0	4.2	—	—	2.30	5.40	—	—	3.10	7.70	10.00	0.55	2.05	2.90	2.44	9.09	12.87	3.76	A	3.80	A	not available
	2.0	5.0	—	—	2.30	6.00	—	—	3.10	8.30	10.00	0.55	2.22	2.90	2.44	9.85	12.87	3.74	A	3.80	A	available
	2.0	7.1	—	—	2.13	6.47	—	—	3.10	8.60	10.00	0.55	2.30	2.90	2.44	10.20	12.87	3.74	A	3.85	A	available
	2.5	2.5	—	—	3.60	3.60	—	—	3.10	7.20	10.00	0.55	1.94	2.90	2.44	8.61	12.87	3.71	A	3.85	A	available
	2.5	3.5	—	—	3.60	4.50	—	—	3.10	8.10	10.00	0.55	2.12	2.90	2.44	9.41	12.87	3.82	A	3.83	A	available
	2.5	4.2	—	—	3.44	5.16	—	—	3.10	8.60	10.00	0.55	2.25	2.90	2.44	9.98	12.87	3.82	A	3.87	A	not available
	2.5	5.0	—	—	3.23	5.38	—	—	3.10	8.60	10.00	0.55	2.22	2.90	2.44	9.85	12.87	3.87	A	3.85	A	available
	2.5	7.1	—	—	2.92	5.68	—	—	3.10	8.60	10.00	0.55	2.22	2.90	2.44	9.85	12.87	3.87	A	3.84	A	available
	3.5	3.5	—	—	4.30	4.30	—	—	3.10	8.60	10.00	0.55	2.22	2.90	2.44	9.85	12.87	3.87	A	3.86	A	available
	3.5	4.2	—	—	3.91	4.69	—	—	3.10	8.60	10.00	0.55	2.22	3.00	2.44	9.85	13.31	3.87	A	3.82	A	not available
	3.5	5.0	—	—	3.51	4.69	—	—	3.10	8.20	10.00	0.55	2.10	3.00	2.44	9.32	13.31	3.90	A	3.80	A	available
	3.5	7.1	—	—	3.37	5.23	—	—	3.10	8.60	10.00	0.55	2.20	3.00	2.44	9.76	13.31	3.91	A	3.84	A	available
	4.2	4.2	—	—	4.30	4.30	—	—	3.10	8.60	10.00	0.55	2.20	3.10	2.44	9.76	13.75	3.91	A	3.86	A	not available
	4.2	5.0	—	—	4.07	4.53	—	—	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.83	A	not available
	4.2	7.1	—	—	3.75	4.85	—	—	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.86	A	not available
	5.0	5.0	—	—	4.30	4.30	—	—	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.86	A	available
	5.0	7.1	—	—	3.97	4.63	—	—	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.87	A	available



Comb.	Combinations				Rated capacity output/kW (Nom. heating)				Total heating capacity(KW)			Total power input(W)			Total current (A)@230V			COP (W/W)	ENERGY LABEL	SCOP (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
TRI (1x3)	2.0	2.0	2.0	—	2.30	2.30	2.30	—	3.10	6.90	9.50	0.55	1.85	3.10	2.44	8.21	13.75	3.73	A	3.80	A	available
	2.0	2.0	2.5	—	2.30	2.30	3.60	—	3.10	8.20	10.00	0.55	2.16	3.10	2.44	9.58	13.75	3.80	A	3.80	A	available
	2.0	2.0	3.5	—	2.17	2.17	4.25	—	3.10	8.60	10.00	0.55	2.26	3.10	2.44	10.03	13.75	3.81	A	3.80	A	available
	2.0	2.0	4.2	—	1.98	1.98	4.64	—	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.80	A	not available
	2.0	2.0	5.0	—	1.87	1.87	4.87	—	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.80	A	available
	2.0	2.0	7.1	—	1.71	1.71	5.19	—	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.80	A	available
	2.0	2.5	2.5	—	2.08	3.26	3.26	—	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.80	A	available
	2.0	2.5	3.5	—	1.90	2.98	3.72	—	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.80	A	available
	2.0	2.5	4.2	—	1.75	2.74	4.11	—	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.80	A	not available
	2.0	2.5	5.0	—	1.66	2.60	4.34	—	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.82	A	available
	2.0	2.5	7.1	—	1.53	2.40	4.67	—	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.82	A	available
	2.0	3.5	3.5	—	1.75	3.42	3.42	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.82	A	available
	2.0	3.5	4.2	—	1.62	3.17	3.81	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.82	A	not available
	2.0	3.5	5.0	—	1.55	3.02	4.03	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.82	A	available
	2.0	3.5	7.1	—	1.43	2.80	4.36	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.82	A	available
	2.0	4.2	4.2	—	1.51	3.55	3.55	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.82	A	not available
	2.0	4.2	5.0	—	1.44	3.39	3.77	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.82	A	not available
	2.0	4.2	7.1	—	1.35	3.16	4.10	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.87	A	not available
	2.5	2.5	2.5	—	2.87	2.87	2.87	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.87	A	available
	2.5	2.5	3.5	—	2.65	2.65	3.31	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.87	A	available
	2.5	2.5	4.2	—	2.46	2.46	3.69	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.87	A	not available
	2.5	2.5	5.0	—	2.35	2.35	3.91	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.87	A	available
	2.5	2.5	7.1	—	2.18	2.18	4.24	—	3.10	8.60	10.00	0.55	2.23	3.10	2.44	9.89	13.75	3.86	A	3.90	A	available
	2.5	3.5	3.5	—	2.46	3.07	3.07	—	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.85	A	available
	2.5	3.5	4.2	—	2.29	2.87	3.44	—	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.85	A	not available
	2.5	3.5	5.0	—	2.20	2.74	3.66	—	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.85	A	available
	2.5	3.5	7.1	—	2.05	2.56	3.99	—	3.10	8.60	10.00	0.55	2.18	3.10	2.44	9.67	13.75	3.94	A	3.85	A	available
	2.5	4.2	4.2	—	2.15	3.23	3.23	—	3.10	8.60	10.00	0.55	2.18	3.10	2.44	9.67	13.75	3.94	A	3.85	A	not available
	2.5	4.2	5.0	—	2.06	3.10	3.44	—	3.10	8.60	10.00	0.55	2.18	3.10	2.44	9.67	13.75	3.94	A	3.85	A	not available
	3.5	3.5	3.5	—	2.87	2.87	2.87	—	3.10	8.60	10.00	0.55	2.18	3.10	2.44	9.67	13.75	3.94	A	3.90	A	available
	3.5	3.5	4.2	—	2.69	2.69	3.23	—	3.10	8.60	10.00	0.55	2.18	3.10	2.44	9.67	13.75	3.94	A	3.90	A	not available
	3.5	3.5	5.0	—	2.58	2.58	3.44	—	3.10	8.60	10.00	0.55	2.18	3.10	2.44	9.67	13.75	3.94	A	3.90	A	available

Comb.	Combinations				Rated capacity output/kW (Nom. heating)				Total heating capacity(KW)			Total power input(W)			Total current (A)@230V			COP (W/W)	ENERGY LABEL	SCOP (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
QUADRI (1x4)	2.0	2.0	2.0	2.0	2.15	2.15	2.15	2.15	3.10	8.60	10.00	0.55	2.25	3.10	2.44	9.98	13.75	3.82	A	3.85	A	available
	2.0	2.0	2.0	2.5	1.88	1.88	1.88	2.95	3.10	8.60	10.00	0.55	2.22	3.10	2.44	9.85	13.75	3.87	A	3.85	A	available
	2.0	2.0	2.0	3.5	1.74	1.74	1.74	3.39	3.10	8.60	10.00	0.55	2.22	3.10	2.44	9.85	13.75	3.87	A	3.85	A	available
	2.0	2.0	2.0	4.2	1.61	1.61	1.61	3.78	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.85	A	not available
	2.0	2.0	2.0	5.0	1.53	1.53	1.53	4.00	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.85	A	available
	2.0	2.0	2.0	7.1	1.42	1.42	1.42	4.33	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.85	A	available
	2.0	2.0	2.5	2.5	1.68	1.68	2.62	2.62	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.85	A	available
	2.0	2.0	2.5	3.5	1.56	1.56	2.44	3.05	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.85	A	available
	2.0	2.0	2.5	4.2	1.45	1.45	2.28	3.41	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.90	A	not available
	2.0	2.0	2.5	5.0	1.39	1.39	2.18	3.63	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.90	A	available
	2.0	2.0	2.5	7.1	1.30	1.30	2.04	3.96	3.10	8.60	10.00	0.55	2.19	3.10	2.44	9.72	13.75	3.93	A	3.90	A	available
	2.0	2.0	3.5	3.5	1.45	1.45	2.85	2.85	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.90	A	available
	2.0	2.0	3.5	4.2	1.36	1.36	2.67	3.20	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.90	A	not available
	2.0	2.0	3.5	5.0	1.31	1.31	2.56	3.42	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.90	A	available
	2.0	2.0	4.2	4.2	1.28	1.28	3.02	3.02	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.90	A	not available
	2.0	2.0	4.2	5.0	1.24	1.24	2.90	3.23	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.90	A	not available
	2.0	2.5	2.5	2.5	1.51	2.36	2.36	2.36	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.90	A	available
	2.0	2.5	2.5	3.5	1.41	2.21	2.21	2.76	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.90	A	available
	2.0	2.5	2.5	4.2	1.33	2.08	2.08	3.12	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.95	A	not available
	2.0	2.5	2.5	5.0	1.28	2.00	2.00	3.33	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.95	A	available
	2.0	2.5	3.5	3.5	1.33	2.08	2.60	2.60	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.95	A	available
	2.0	2.5	3.5	4.2	1.25	1.96	2.45	2.94	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.95	A	not available
	2.0	2.5	3.5	5.0	1.21	1.89	2.36	3.15	3.10	8.60	10.00	0.55	2.17	3.10	2.44	9.63	13.75	3.96	A	3.95	A	available
	2.0	2.5	4.2	4.2	1.18	1.85	2.78	2.78	3.10	8.60	10.00	0.55	2.15	3.10	2.44	9.54	13.75	4.00	A	3.95	A	not available
	2.0	2.5	4.2	5.0	1.14	1.79	2.68	2.98	3.10	8.60	10.00	0.55	2.15	3.10	2.44	9.54	13.75	4.00	A	3.95	A	not available
	2.0	3.5	3.5	3.5	1.25	2.45	2.45	2.45	3.10	8.60	10.00	0.55	2.15	3.10	2.44	9.54	13.75	4.00	A	3.95	A	available
	2.0	3.5	3.5	4.2	1.18	2.32	2.32	2.78	3.10	8.60	10.00	0.55	2.15	3.10	2.44	9.54	13.75	4.00	A	4.00	A+	not available
	2.5	2.5	2.5	2.5	2.15	2.15	2.15	2.15	3.10	8.60	10.00	0.55	2.15	3.10	2.44	9.54	13.75	4.00	A	4.00	A+	available
	2.5	2.5	2.5	3.5	2.02	2.02	2.02	2.53	3.10	8.60	10.00	0.55	2.15	3.10	2.44	9.54	13.75	4.00	A	4.00	A+	available
	2.5	2.5	2.5	4.2	1.91	1.91	1.91	2.87	3.10	8.60	10.00	0.55	2.15	3.10	2.44	9.54	13.75	4.00	A	4.00	A+	not available
2.5	2.5	3.5	3.5	1.91	1.91	2.39	2.39	3.10	8.60	10.00	0.55	2.15	3.10	2.44	9.54	13.75	4.00	A	4.00	A+	available	

**4U85S2SR2FA combination and the data**  
**COOLING 8.5**

Comb.	Combinations				Rated capacity output/kW (Nom. cooling)				Total cooling capacity(kW)			Total power input (kW)			Total current (A)@230V			EER (W/W)	ENERGY LABEL	SEER (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
1x1	2.0	—	—	—	2.00	—	—	—	0.80	2.00	2.80	0.55	0.66	1.30	2.44	2.93	5.77	3.03	B	6.20	A++	not available
	2.5	—	—	—	2.60	—	—	—	0.80	2.60	3.90	0.55	0.86	1.34	2.44	3.82	5.93	3.02	B	6.20	A++	not available
	3.5	—	—	—	3.60	—	—	—	1.00	3.60	5.30	0.55	1.20	1.50	2.44	5.32	6.65	3.00	B	6.20	A++	not available
	4.2	—	—	—	4.40	—	—	—	1.30	4.40	5.00	0.55	1.40	1.90	2.44	6.21	8.43	3.14	B	6.20	A++	not available
	5.0	—	—	—	5.20	—	—	—	1.40	5.20	7.00	0.55	1.65	1.90	2.44	7.32	8.43	3.15	B	6.20	A++	not available
	7.1	—	—	—	6.50	—	—	—	1.50	6.50	7.40	0.55	2.00	3.00	2.44	8.87	13.31	3.25	A	6.20	A++	not available
BI (1x2)	2.0	2.0	—	—	2.00	2.00	—	—	2.50	4.00	5.60	0.55	1.30	3.20	2.44	5.77	14.20	3.08	B	6.20	A++	available
	2.0	2.5	—	—	2.00	2.60	—	—	2.50	4.60	6.70	0.55	1.50	3.20	2.44	6.65	14.20	3.07	B	6.20	A++	available
	2.0	3.5	—	—	2.00	3.60	—	—	2.50	5.60	8.10	0.55	1.80	3.20	2.44	7.99	14.20	3.11	B	6.20	A++	available
	2.0	4.2	—	—	2.00	4.40	—	—	2.50	6.40	7.80	0.55	2.05	3.20	2.44	9.09	14.20	3.12	B	6.20	A++	not available
	2.0	5.0	—	—	2.00	5.20	—	—	2.50	7.20	9.30	0.55	2.28	3.20	2.44	10.12	14.20	3.16	B	6.20	A++	available
	2.0	7.1	—	—	2.00	6.50	—	—	2.50	8.50	9.30	0.55	2.65	3.30	2.44	11.76	14.64	3.21	A	6.20	A++	available
	2.5	2.5	—	—	2.60	2.60	—	—	2.50	5.20	7.80	0.55	1.60	3.30	2.44	7.10	14.64	3.25	A	6.20	A++	available
	2.5	3.5	—	—	2.60	3.60	—	—	2.50	6.20	9.10	0.55	1.98	3.30	2.44	8.78	14.64	3.13	B	6.20	A++	available
	2.5	4.2	—	—	2.60	4.40	—	—	2.50	7.00	9.30	0.55	2.20	3.30	2.44	9.76	14.64	3.18	B	6.20	A++	not available
	2.5	5.0	—	—	2.60	5.20	—	—	2.50	7.80	9.30	0.55	2.35	3.30	2.44	10.43	14.64	3.32	A	6.20	A++	available
	2.5	7.1	—	—	2.43	6.07	—	—	2.50	8.50	9.30	0.55	2.60	3.30	2.44	11.54	14.64	3.27	A	6.20	A++	available
	3.5	3.5	—	—	3.60	3.60	—	—	2.50	7.20	9.30	0.55	2.20	3.30	2.44	9.76	14.64	3.27	A	6.20	A++	available
	3.5	4.2	—	—	3.60	4.40	—	—	2.50	8.00	9.30	0.55	2.42	3.30	2.44	10.74	14.64	3.31	A	6.20	A++	not available
	3.5	5.0	—	—	3.31	4.79	—	—	2.50	8.10	9.50	0.55	2.52	3.30	2.44	11.18	14.64	3.21	A	6.20	A++	available
	3.5	7.1	—	—	3.03	5.47	—	—	2.50	8.50	9.50	0.55	2.59	3.30	2.44	11.49	14.64	3.28	A	6.20	A++	available
	4.2	4.2	—	—	4.25	4.25	—	—	2.50	8.50	9.50	0.55	2.59	3.30	2.44	11.49	14.64	3.28	A	6.20	A++	not available
	4.2	5.0	—	—	3.90	4.60	—	—	2.50	8.50	9.50	0.55	2.59	3.30	2.44	11.49	14.64	3.28	A	6.20	A++	not available
	4.2	7.1	—	—	3.43	5.07	—	—	2.50	8.50	9.50	0.55	2.58	3.30	2.44	11.45	14.64	3.29	A	6.20	A++	not available
	5.0	5.0	—	—	4.25	4.25	—	—	2.50	8.50	9.50	0.55	2.56	3.30	2.44	11.36	14.64	3.32	A	6.20	A++	available
	5.0	7.1	—	—	3.78	4.72	—	—	2.50	8.50	9.50	0.55	2.55	3.30	2.44	11.31	14.64	3.33	A	6.20	A++	available
7.1	7.1	—	—	4.25	4.25	—	—	2.50	8.50	9.50	0.55	2.55	3.30	2.44	11.31	14.64	3.33	A	6.20	A++	available	

Comb.	Combinations				Rated capacity output/ kW (Nom. cooling)				Total cooling capacity(kW)			Total power input (kW)			Total current (A)@230V			EER (W/W)	ENERGY LABEL	SEER (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
TRI (1x3)	2.0	2.0	2.0	—	2.00	2.00	2.00	—	3.00	6.00	9.50	0.55	1.85	3.50	2.44	8.21	15.53	3.24	A	6.70	A++	available
	2.0	2.0	2.5	—	2.00	2.00	2.60	—	3.00	6.60	9.50	0.55	2.00	3.50	2.44	8.87	15.53	3.30	A	6.70	A++	available
	2.0	2.0	3.5	—	2.00	2.00	3.60	—	3.00	7.60	9.50	0.55	2.30	3.50	2.44	10.20	15.53	3.30	A	6.70	A++	available
	2.0	2.0	4.2	—	2.00	2.00	4.40	—	3.20	8.40	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.28	A	6.70	A++	not available
	2.0	2.0	5.0	—	1.85	1.85	4.80	—	3.20	8.50	9.50	0.55	2.57	3.50	2.44	11.40	15.53	3.31	A	6.70	A++	available
	2.0	2.0	7.1	—	1.62	1.62	5.26	—	3.20	8.50	9.50	0.55	2.57	3.50	2.44	11.40	15.53	3.31	A	6.70	A++	available
	2.0	2.5	2.5	—	2.00	2.60	2.60	—	3.20	7.20	9.50	0.55	2.20	3.50	2.44	9.76	15.53	3.27	A	6.70	A++	available
	2.0	2.5	3.5	—	2.00	2.60	3.60	—	3.20	8.20	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.28	A	6.70	A++	available
	2.0	2.5	4.2	—	1.89	2.46	4.16	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	not available
	2.0	2.5	5.0	—	1.73	2.26	4.51	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	available
	2.0	2.5	7.1	—	1.53	1.99	4.98	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	available
	2.0	3.5	3.5	—	1.85	3.33	3.33	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	available
	2.0	3.5	4.2	—	1.70	3.06	3.74	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	not available
	2.0	3.5	5.0	—	1.57	2.83	4.09	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	available
	2.0	3.5	7.1	—	1.40	2.53	4.57	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	available
	2.0	4.2	4.2	—	1.57	3.46	3.46	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	not available
	2.0	4.2	5.0	—	1.47	3.22	3.81	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	not available
	2.0	4.2	7.1	—	1.32	2.90	4.28	—	3.20	8.50	9.50	0.55	2.56	3.50	2.44	11.36	15.53	3.32	A	6.70	A++	not available
	2.5	2.5	2.5	—	2.60	2.60	2.60	—	3.20	7.80	9.50	0.55	2.35	3.50	2.44	10.43	15.53	3.32	A	6.72	A++	available
	2.5	2.5	3.5	—	2.51	2.51	3.48	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.72	A++	available
	2.5	2.5	4.2	—	2.30	2.30	3.90	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.74	A++	not available
	2.5	2.5	5.0	—	2.13	2.13	4.25	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.74	A++	available
	2.5	2.5	7.1	—	1.89	1.89	4.72	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.70	A++	available
	2.5	3.5	3.5	—	2.26	3.12	3.12	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.73	A++	available
	2.5	3.5	4.2	—	2.08	2.89	3.53	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.70	A++	not available
	2.5	3.5	5.0	—	1.94	2.68	3.88	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.70	A++	available
	2.5	3.5	7.1	—	1.74	2.41	4.35	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.70	A++	available
	2.5	4.2	4.2	—	1.94	3.28	3.28	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.70	A++	not available
	2.5	4.2	5.0	—	1.81	3.07	3.62	—	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.70	A++	not available
	3.5	3.5	3.5	—	2.83	2.83	2.83	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.75	A++	available
	3.5	3.5	4.2	—	2.64	2.64	3.22	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.70	A++	not available
	3.5	3.5	5.0	—	2.47	2.47	3.56	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.70	A++	available
	3.5	3.5	7.1	—	2.23	2.23	4.03	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.70	A++	available
	3.5	4.2	4.2	—	2.47	3.02	3.02	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.75	A++	not available
	3.5	4.2	5.0	—	2.32	2.83	3.35	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.75	A++	not available
	3.5	5.0	5.0	—	2.19	3.16	3.16	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.75	A++	available
4.2	4.2	4.2	—	2.83	2.83	2.83	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.75	A++	not available	
4.2	4.2	5.0	—	2.67	2.67	3.16	—	3.20	8.50	9.50	0.55	2.53	3.50	2.44	11.22	15.53	3.36	A	6.75	A++	not available	

Comb.	Combinations				Rated capacity output/ kW (Nom. cooling)				Total cooling capacity(kW)			Total power input (kW)			Total current (A)@230V			EER (W/W)	ENERGY LABEL	SEER (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
QUADRI (1x4)	2.0	2.0	2.0	2.0	2.00	2.00	2.00	2.00	3.20	8.00	9.50	0.55	2.43	3.50	2.44	10.78	15.53	3.29	A	6.80	A++	available
	2.0	2.0	2.0	2.5	1.98	1.98	1.98	2.57	3.20	8.50	9.50	0.55	2.55	3.50	2.44	11.31	15.53	3.33	A	6.80	A++	available
	2.0	2.0	2.0	3.5	1.77	1.77	1.77	3.19	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.80	A++	available
	2.0	2.0	2.0	4.2	1.63	1.63	1.63	3.60	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.80	A++	not available
	2.0	2.0	2.0	5.0	1.52	1.52	1.52	3.95	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.80	A++	available
	2.0	2.0	2.0	7.1	1.36	1.36	1.36	4.42	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.70	A++	available
	2.0	2.0	2.5	2.5	1.85	1.85	2.40	2.40	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.80	A++	available
	2.0	2.0	2.5	3.5	1.67	1.67	2.17	3.00	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.80	A++	available
	2.0	2.0	2.5	4.2	1.55	1.55	2.01	3.40	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.80	A++	not available
	2.0	2.0	2.5	5.0	1.44	1.44	1.87	3.75	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.80	A++	available
	2.0	2.0	2.5	7.1	1.30	1.30	1.69	4.22	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.70	A++	available
	2.0	2.0	3.5	3.5	1.52	1.52	2.73	2.73	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.80	A++	available
	2.0	2.0	3.5	4.2	1.42	1.42	2.55	3.12	3.20	8.50	9.50	0.55	2.54	3.50	2.44	11.27	15.53	3.35	A	6.70	A++	not available
	2.0	2.0	3.5	5.0	1.33	1.33	2.39	3.45	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	6.70	A++	available
	2.0	2.0	4.2	4.2	1.33	1.33	2.92	2.92	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	not available
	2.0	2.0	4.2	5.0	1.25	1.25	2.75	3.25	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	not available
	2.0	2.5	2.5	2.5	1.73	2.26	2.26	2.26	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	available
	2.0	2.5	2.5	3.5	1.57	2.05	2.05	2.83	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	available
	2.0	2.5	2.5	4.2	1.47	1.91	1.91	3.22	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	not available
	2.0	2.5	2.5	5.0	1.37	1.78	1.78	3.56	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	available
	2.0	2.5	3.5	3.5	1.44	1.87	2.59	2.59	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	available
	2.0	2.5	3.5	4.2	1.35	1.75	2.43	2.97	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	not available
	2.0	2.5	3.5	5.0	1.27	1.65	2.28	3.30	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	available
	2.0	2.5	4.2	4.2	1.27	1.65	2.79	2.79	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	not available
	2.0	2.5	4.2	5.0	1.20	1.56	2.63	3.11	3.20	8.50	9.50	0.55	2.52	3.50	2.44	11.18	15.53	3.37	A	7.00	A++	not available
	2.0	3.5	3.5	3.5	1.33	2.39	2.39	2.39	3.20	8.50	9.50	0.55	2.51	3.50	2.44	11.14	15.53	3.39	A	7.00	A++	available
	2.0	3.5	3.5	4.2	1.25	2.25	2.25	2.75	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	not available
	2.5	2.5	2.5	2.5	2.13	2.13	2.13	2.13	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	available
	2.5	2.5	2.5	3.5	1.94	1.94	1.94	2.68	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	available
	2.5	2.5	2.5	4.2	1.81	1.81	1.81	3.07	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	not available
	2.5	2.5	2.5	5.0	1.70	1.70	1.70	3.40	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	available
	2.5	2.5	3.5	3.5	1.78	1.78	2.47	2.47	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	available
	2.5	2.5	3.5	4.2	1.67	1.67	2.32	2.83	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	not available
	2.5	2.5	3.5	5.0	1.58	1.58	2.19	3.16	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	available
	2.5	2.5	4.2	4.2	1.58	1.58	2.67	2.67	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	not available
	2.5	3.5	3.5	3.5	1.65	2.28	2.28	2.28	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	available
	2.5	3.5	3.5	4.2	1.56	2.15	2.15	2.63	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	available
	3.5	3.5	3.5	3.5	2.13	2.13	2.13	2.13	3.20	8.50	9.50	0.55	2.50	3.50	2.44	11.09	15.53	3.40	A	7.00	A++	available

## 4U85S2SR2FA combination and the data HEATING 9.6

Comb.	Combinations				Rated capacity output/kW (Nom. heating)				Total heating capacity(KW)			Total power input(W)			Total current (A)@230V			COP (W/W)	ENERGY LABEL	SCOP (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
1x1	2.0	—	—	—	2.30	—	—	—	0.80	2.30	4.00	0.55	0.63	1.50	2.44	2.80	6.65	3.65	A	3.70	A	not available
	2.5	—	—	—	3.60	—	—	—	0.80	3.60	6.00	0.55	0.98	1.40	2.44	4.35	6.21	3.67	A	3.70	A	not available
	3.5	—	—	—	4.50	—	—	—	1.00	4.50	6.00	0.55	1.21	1.50	2.44	5.37	6.65	3.72	A	3.70	A	not available
	4.2	—	—	—	5.40	—	—	—	1.50	5.40	6.00	0.55	1.44	1.90	2.44	6.39	8.43	3.75	A	3.70	A	not available
	5.0	—	—	—	6.00	—	—	—	1.50	6.00	8.00	0.55	1.59	2.60	2.44	7.05	11.54	3.77	A	3.70	A	not available
	7.1	—	—	—	7.00	—	—	—	1.50	7.00	8.60	0.55	1.83	2.60	2.44	8.12	11.54	3.83	A	3.70	A	not available
BI (1x2)	2.0	2.0	—	—	2.30	2.30	—	—	2.80	4.60	8.00	0.55	1.25	3.30	2.44	5.55	14.64	3.68	A	3.75	A	available
	2.0	2.5	—	—	2.30	3.60	—	—	3.00	5.90	10.00	0.55	1.59	3.30	2.44	7.05	14.64	3.71	A	3.75	A	available
	2.0	3.5	—	—	2.30	4.50	—	—	3.20	6.80	10.00	0.55	1.83	3.30	2.44	8.12	14.64	3.72	A	3.75	A	available
	2.0	4.2	—	—	2.30	5.40	—	—	3.40	7.70	10.00	0.55	2.05	3.30	2.44	9.09	14.64	3.76	A	3.80	A	not available
	2.0	5.0	—	—	2.30	6.00	—	—	3.80	8.30	10.50	0.55	2.22	3.30	2.44	9.85	14.64	3.74	A	3.80	A	available
	2.0	7.1	—	—	2.30	7.00	—	—	4.00	9.30	10.50	0.55	2.50	3.30	2.44	11.09	14.64	3.72	A	3.85	A	available
	2.5	2.5	—	—	3.60	3.60	—	—	3.40	7.20	10.50	0.55	1.94	3.30	2.44	8.61	14.64	3.71	A	3.85	A	available
	2.5	3.5	—	—	3.60	4.50	—	—	3.80	8.10	10.50	0.55	2.10	3.30	2.44	9.32	14.64	3.86	A	3.83	A	available
	2.5	4.2	—	—	3.60	5.40	—	—	4.00	9.00	10.50	0.55	2.30	3.30	2.44	10.20	14.64	3.91	A	3.87	A	not available
	2.5	5.0	—	—	3.60	6.00	—	—	4.40	9.60	10.50	0.55	2.50	3.30	2.44	11.09	14.64	3.84	A	3.85	A	available
	2.5	7.1	—	—	3.26	6.34	—	—	4.40	9.60	10.50	0.55	2.55	3.30	2.44	11.31	14.64	3.76	A	3.84	A	available
	3.5	3.5	—	—	4.50	4.50	—	—	4.00	9.00	10.50	0.55	2.35	3.30	2.44	10.43	14.64	3.83	A	3.86	A	available
	3.5	4.2	—	—	4.36	5.24	—	—	4.40	9.60	10.50	0.55	2.50	3.30	2.44	11.09	14.64	3.84	A	3.82	A	not available
	3.5	5.0	—	—	3.86	5.14	—	—	4.40	9.00	10.50	0.55	2.37	3.30	2.44	10.51	14.64	3.80	A	3.80	A	available
	3.5	7.1	—	—	3.76	5.84	—	—	4.40	9.60	10.50	0.55	2.50	3.30	2.44	11.09	14.64	3.84	A	3.84	A	available
	4.2	4.2	—	—	4.80	4.80	—	—	4.40	9.60	10.50	0.55	2.49	3.30	2.44	11.05	14.64	3.86	A	3.86	A	not available
	4.2	5.0	—	—	4.55	5.05	—	—	4.40	9.60	10.50	0.55	2.49	3.30	2.44	11.05	14.64	3.86	A	3.83	A	not available
	4.2	7.1	—	—	4.18	5.42	—	—	4.40	9.60	10.50	0.55	2.48	3.30	2.44	11.00	14.64	3.87	A	3.86	A	not available
	5.0	5.0	—	—	4.80	4.80	—	—	4.40	9.60	10.50	0.55	2.46	3.30	2.44	10.91	14.64	3.90	A	3.86	A	available
	5.0	7.1	—	—	4.43	5.17	—	—	4.40	9.60	10.50	0.55	2.48	3.30	2.44	11.00	14.64	3.87	A	3.87	A	available
7.1	7.1	—	—	4.80	4.80	—	—	4.40	9.60	10.50	0.55	2.50	3.30	2.44	11.09	14.64	3.84	A	3.85	A	available	

Comb.	Combinations				Rated capacity output/kW (Nom. heating)				Total heating capacity(KW)			Total power input(W)			Total current (A)@230V			COP (W/W)	ENERGY LABEL	SCOP (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
TRI (1x3)	2.0	2.0	2.0	—	2.30	2.30	2.30	—	3.80	6.90	10.50	0.55	1.85	3.40	2.44	8.21	15.08	3.73	A	3.80	A	available
	2.0	2.0	2.5	—	2.30	2.30	3.60	—	4.00	8.20	10.50	0.55	2.16	3.40	2.44	9.58	15.08	3.80	A	3.80	A	available
	2.0	2.0	3.5	—	2.30	2.30	4.50	—	4.20	9.10	10.50	0.55	2.39	3.40	2.44	10.60	15.08	3.81	A	3.80	A	available
	2.0	2.0	4.2	—	2.21	2.21	5.18	—	4.40	9.60	10.50	0.55	2.48	3.40	2.44	11.00	15.08	3.87	A	3.80	A	not available
	2.0	2.0	5.0	—	2.08	2.08	5.43	—	4.40	9.60	10.50	0.55	2.48	3.40	2.44	11.00	15.08	3.87	A	3.80	A	available
	2.0	2.0	7.1	—	1.90	1.90	5.79	—	4.40	9.60	10.50	0.55	2.50	3.40	2.44	11.09	15.08	3.84	A	3.80	A	available
	2.0	2.5	2.5	—	2.32	3.64	3.64	—	4.40	9.60	10.50	0.55	2.54	3.40	2.44	11.27	15.08	3.78	A	3.80	A	available
	2.0	2.5	3.5	—	2.12	3.32	4.15	—	4.40	9.60	10.50	0.55	2.48	3.40	2.44	11.00	15.08	3.87	A	3.80	A	available
	2.0	2.5	4.2	—	1.95	3.06	4.59	—	4.40	9.60	10.50	0.55	2.48	3.40	2.44	11.00	15.08	3.87	A	3.80	A	not available
	2.0	2.5	5.0	—	1.86	2.90	4.84	—	4.40	9.60	10.50	0.55	2.47	3.40	2.44	10.96	15.08	3.89	A	3.82	A	available
	2.0	2.5	7.1	—	1.71	2.68	5.21	—	4.40	9.60	10.50	0.55	2.50	3.40	2.44	11.09	15.08	3.84	A	3.82	A	available
	2.0	3.5	3.5	—	1.95	3.82	3.82	—	4.40	9.60	10.50	0.55	2.52	3.40	2.44	11.18	15.08	3.81	A	3.82	A	available
	2.0	3.5	4.2	—	1.81	3.54	4.25	—	4.40	9.60	10.50	0.55	2.46	3.40	2.44	10.91	15.08	3.90	A	3.82	A	not available
	2.0	3.5	5.0	—	1.73	3.38	4.50	—	4.40	9.60	10.50	0.55	2.46	3.40	2.44	10.91	15.08	3.90	A	3.82	A	available
	2.0	3.5	7.1	—	1.60	3.13	4.87	—	4.40	9.60	10.50	0.55	2.46	3.40	2.44	10.91	15.08	3.90	A	3.82	A	available
	2.0	4.2	4.2	—	1.69	3.96	3.96	—	4.40	9.60	10.50	0.55	2.46	3.40	2.44	10.91	15.08	3.90	A	3.82	A	not available
	2.0	4.2	5.0	—	1.61	3.78	4.20	—	4.40	9.60	10.50	0.55	2.46	3.40	2.44	10.91	15.08	3.90	A	3.82	A	not available
	2.0	4.2	7.1	—	1.50	3.53	4.57	—	4.40	9.60	10.50	0.55	2.46	3.40	2.44	10.91	15.08	3.90	A	3.87	A	not available
	2.5	2.5	2.5	—	3.20	3.20	3.20	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.87	A	available
	2.5	2.5	3.5	—	2.95	2.95	3.69	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.87	A	available
	2.5	2.5	4.2	—	2.74	2.74	4.11	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.87	A	not available
	2.5	2.5	5.0	—	2.62	2.62	4.36	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.87	A	available
	2.5	2.5	7.1	—	2.43	2.43	4.73	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.90	A	available
	2.5	3.5	3.5	—	2.74	3.43	3.43	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.85	A	available
	2.5	3.5	4.2	—	2.56	3.20	3.84	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.85	A	not available
	2.5	3.5	5.0	—	2.45	3.06	4.09	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.85	A	available
	2.5	3.5	7.1	—	2.29	2.86	4.45	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.85	A	available
	2.5	4.2	4.2	—	2.40	3.60	3.60	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.85	A	not available
	2.5	4.2	5.0	—	2.30	3.46	3.84	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.85	A	not available
	3.5	3.5	3.5	—	3.20	3.20	3.20	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.90	A	available
	3.5	3.5	4.2	—	3.00	3.00	3.60	—	4.40	9.60	10.50	0.55	2.45	3.40	2.44	10.87	15.08	3.92	A	3.90	A	not available
	3.5	3.5	5.0	—	2.88	2.88	3.84	—	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	available
	3.5	3.5	7.1	—	2.70	2.70	4.20	—	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.85	A	available
	3.5	4.2	4.2	—	2.82	3.39	3.39	—	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	not available
	3.5	4.2	5.0	—	2.72	3.26	3.62	—	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	not available
	3.5	5.0	5.0	—	2.62	3.49	3.49	—	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	available
	4.2	4.2	4.2	—	3.20	3.20	3.20	—	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	not available
	4.2	4.2	5.0	—	3.09	3.09	3.43	—	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	not available

Comb.	Combinations				Rated capacity output/kW (Nom. heating)				Total heating capacity(KW)			Total power input(W)			Total current (A)@230V			COP (W/W)	ENERGY LABEL	SCOP (W/W)	ENERGY LABEL	REMARKS
	Unit A	Unit B	Unit C	Unit D	Unit A	Unit B	Unit C	Unit D	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Min. data	Rated data	Max. data	Rated capacity				
QUADRI (1x4)	2.0	2.0	2.0	2.0	2.30	2.30	2.30	2.30	4.20	9.20	10.50	0.55	2.42	3.40	2.44	10.74	15.08	3.80	A	3.85	A	available
	2.0	2.0	2.0	2.5	2.10	2.10	2.10	3.29	4.20	9.60	10.50	0.55	2.44	3.40	2.44	10.83	15.08	3.93	A	3.85	A	available
	2.0	2.0	2.0	3.5	1.94	1.94	1.94	3.79	4.40	9.60	10.50	0.55	2.44	3.40	2.44	10.83	15.08	3.93	A	3.85	A	available
	2.0	2.0	2.0	4.2	1.80	1.80	1.80	4.21	4.40	9.60	10.50	0.55	2.44	3.40	2.44	10.83	15.08	3.93	A	3.85	A	not available
	2.0	2.0	2.0	5.0	1.71	1.71	1.71	4.47	4.40	9.60	10.50	0.55	2.44	3.40	2.44	10.83	15.08	3.93	A	3.85	A	available
	2.0	2.0	2.0	7.1	1.59	1.59	1.59	4.83	4.40	9.60	10.50	0.55	2.44	3.40	2.44	10.83	15.08	3.93	A	3.85	A	available
	2.0	2.0	2.5	2.5	1.87	1.87	2.93	2.93	4.40	9.60	10.50	0.55	2.44	3.40	2.44	10.83	15.08	3.93	A	3.85	A	available
	2.0	2.0	2.5	3.5	1.74	1.74	2.72	3.40	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.85	A	available
	2.0	2.0	2.5	4.2	1.62	1.62	2.54	3.81	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	not available
	2.0	2.0	2.5	5.0	1.55	1.55	2.43	4.06	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	available
	2.0	2.0	2.5	7.1	1.45	1.45	2.27	4.42	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	available
	2.0	2.0	3.5	3.5	1.62	1.62	3.18	3.18	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	available
	2.0	2.0	3.5	4.2	1.52	1.52	2.98	3.58	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	not available
	2.0	2.0	3.5	5.0	1.46	1.46	2.86	3.81	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	available
	2.0	2.0	4.2	4.2	1.43	1.43	3.37	3.37	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	not available
	2.0	2.0	4.2	5.0	1.38	1.38	3.24	3.60	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	not available
	2.0	2.5	2.5	2.5	1.69	2.64	2.64	2.64	4.40	9.60	10.50	0.55	2.43	3.40	2.44	10.78	15.08	3.95	A	3.90	A	available
	2.0	2.5	2.5	3.5	1.58	2.47	2.47	3.09	4.40	9.60	10.50	0.55	2.42	3.40	2.44	10.74	15.08	3.97	A	3.90	A	available
	2.0	2.5	2.5	4.2	1.48	2.32	2.32	3.48	4.40	9.60	10.50	0.55	2.42	3.40	2.44	10.74	15.08	3.97	A	3.95	A	not available
	2.0	2.5	2.5	5.0	1.42	2.23	2.23	3.72	4.40	9.60	10.50	0.55	2.42	3.40	2.44	10.74	15.08	3.97	A	3.95	A	available
	2.0	2.5	3.5	3.5	1.48	2.32	2.90	2.90	4.40	9.60	10.50	0.55	2.42	3.40	2.44	10.74	15.08	3.97	A	3.95	A	available
	2.0	2.5	3.5	4.2	1.40	2.19	2.73	3.28	4.40	9.60	10.50	0.55	2.42	3.40	2.44	10.74	15.08	3.97	A	3.95	A	not available
	2.0	2.5	3.5	5.0	1.35	2.11	2.63	3.51	4.40	9.60	10.50	0.55	2.42	3.40	2.44	10.74	15.08	3.97	A	3.95	A	available
	2.0	2.5	4.2	4.2	1.32	2.07	3.10	3.10	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	3.95	A	not available
	2.0	2.5	4.2	5.0	1.28	2.00	3.00	3.33	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	3.95	A	not available
	2.0	3.5	3.5	3.5	1.40	2.73	2.73	2.73	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	3.95	A	available
	2.0	3.5	3.5	4.2	1.32	2.59	2.59	3.10	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	not available
	2.5	2.5	2.5	2.5	2.40	2.40	2.40	2.40	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	available
	2.5	2.5	2.5	3.5	2.26	2.26	2.26	2.82	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	available
	2.5	2.5	2.5	4.2	2.13	2.13	2.13	3.20	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	not available
	2.5	2.5	2.5	5.0	2.06	2.06	2.06	3.43	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	available
	2.5	2.5	3.5	3.5	2.13	2.13	2.67	2.67	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	available
	2.5	2.5	3.5	4.2	2.02	2.02	2.53	3.03	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	not available
	2.5	2.5	3.5	5.0	1.95	1.95	2.44	3.25	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	available
	2.5	2.5	4.2	4.2	1.68	1.68	3.12	3.12	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	not available
	2.5	3.5	3.5	3.5	2.02	2.53	2.53	2.53	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	available
2.5	3.5	3.5	4.2	1.92	2.40	2.40	2.88	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	available	
3.5	3.5	3.5	3.5	2.40	2.40	2.40	2.40	4.40	9.60	10.50	0.55	2.40	3.40	2.44	10.65	15.08	4.00	A	4.00	A+	available	